



SAFETY DATA SHEET

OCEANSIDE DETAILING PRODUCTS


PREMIUM WHEEL & TIRE CLEANER

DRAFT - FINISHED DILUTION CLASSIFICATION AND AUTHORIZED EMERGENCY NUMBER PENDING

1 - PRODUCT IDENTIFICATION

PRODUCT NAME: Oceanside Detailing Products Premium Wheel & Tire Cleaner
PRODUCT TYPE: Alkaline liquid wheel, tire and brake-dust cleaning compound
PRODUCT IDENTIFIER: Premium Wheel & Tire Cleaner
PRODUCT NUMBER: ODP-WTC
RESPONSIBLE PARTY: Oceanside Detailing Products
ADDRESS: PO Box 229, Deep River, CT 06417
BUSINESS PHONE: 860-333-8675
WEBSITE: www.oceansidedetailingproducts.com
EMERGENCY PHONE: CHEMTREC - pending registration/authorization. Insert authorized emergency number before final commercial distribution.

2 - HAZARDS IDENTIFICATION



CLASSIFICATION OF SUBSTANCE/MIXTURE: Skin Corrosion (1); Serious Eye Damage (1); Corrosive to Metals (1); Acute Toxicity, Oral (5).

SIGNAL WORD: DANGER!

HAZARD STATEMENTS: Causes severe skin burns and eye damage. May be corrosive to metals. May be harmful if swallowed.

PREVENTION: Do not breathe dusts or mists. Wash hands thoroughly after handling. Do not touch eyes. Wear protective gloves / protective clothing / eye protection / face protection. Keep only in original packaging.

RESPONSE: Absorb spillage to prevent material damage. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Get medical help. IF ON SKIN: Take off immediately all contaminated clothing. Immediately rinse with water for several minutes. Wash contaminated clothing before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get emergency medical help immediately. IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical help.

STORAGE: Store locked up. Store in a corrosion-resistant container with a resistant inner liner.

DISPOSAL: Dispose of container and contents in accordance with local regulations.

Classification above is carried from the upstream concentrate SDS as a conservative draft basis. The final Oceanside classification must reflect the concentration actually sold.

3 - COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT	C.A.S. NUMBER
Water	7732-18-5
Sodium hydroxide	1310-73-2
2-Butoxyethanol	111-76-2
Sodium (C14-16) olefin sulfonate	68439-57-6
Tetrasodium ethylenediaminetetraacetate	64-02-8
Sodium xylenesulfonate	1300-72-7

If percentages, chemical names or C.A.S. numbers are not listed, they may be withheld as trade secret information or may not be required under OSHA Hazard Communication Standard 29 CFR 1910.1200. Information is to be disclosed as required to authorized individuals.

4 - FIRST-AID MEASURES

BREATHING (INHALATION): Maintain adequate ventilation in work area. If signs of discomfort or irritation occur, remove to fresh air. If burns occur or symptoms persist, get immediate medical attention.

SWALLOWING (INGESTION): DO NOT INDUCE VOMITING! Rinse mouth, then drink a large quantity of water or milk. Do not attempt to give liquids to an unconscious person. Get immediate medical attention.

EYES: Flush eyes with a large quantity of fresh water for at least 15 minutes. Apply ice compresses and get immediate medical attention by an eye specialist. It may be necessary to bring the person to a hospital emergency room.



SAFETY DATA SHEET

OCEANSIDE DETAILING PRODUCTS

PREMIUM WHEEL & TIRE CLEANER

SKIN (DERMAL):

Immediately take off all contaminated clothing. Flush skin with a large quantity of fresh water for several minutes. If burns occur or irritation persists, get immediate medical attention. Wash contaminated clothing before reuse.

5 - FIRE-FIGHTING MEASURES

FLASHPOINT:

This product is non-flammable.

EXTINGUISHING MEDIA:

Use extinguishing media suitable for materials already burning.

SPECIAL FIRE-FIGHTING PROCEDURES:

Firefighters working in areas where this product is present should be equipped with an approved, fully enclosed SCBA.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

None known.

6 - ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES:

Dike and absorb spillage to prevent release into streams or sewer systems, as well as material damage. Consult local, state and federal authorities.

WASTE DISPOSAL:

As recommended by local, state and federal authorities.

7 - HANDLING AND STORAGE

STORAGE:

Store in a cool, well-ventilated area. Avoid overheating or freezing. Store locked up. Keep only in original packaging or in a corrosion-resistant container. Do NOT store this product in an unmarked container.

HANDLING:

Maintain adequate ventilation of work area. Wear eye, face and skin protection if product is likely to splash. Avoid breathing product mist and spray. Do NOT transfer this product to an unmarked container. Spilled material is slippery. Keep away from children.

ATTENTION:

Do NOT reuse empty container. Empty containers retain vapor and product residue, which can be dangerous.

8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION:

Not usually needed in well-ventilated areas. If needed, use a NIOSH-approved respirator.

PROTECTIVE CLOTHING:

Nitrile or PVC gloves, chemical splash goggles, protective outerwear and boots.

ADDITIONAL MEASURES:

Under normal use according to label instructions, special protection should not be necessary. Wear eye, face and skin protection if product is likely to splash. Keep away from children.

INGREDIENT	C.A.S. NUMBER	OSHA PEL / LIMIT
Water	7732-18-5	No limits established
Sodium hydroxide	1310-73-2	2 mg/m3
2-Butoxyethanol	111-76-2	50 ppm, 240 mg/m3
Sodium (C14-16) olefin sulfonate	68439-57-6	No limits established
Tetrasodium ethylenediaminetetraacetate	64-02-8	No limits established
Sodium xylenesulfonate	1300-72-7	No limits established

When OSHA 8-hour TWA, STEL, or Ceiling values are not established, the upstream SDS may report NIOSH REL, ACGIH TLV, or AIHA WEEL values as applicable.

9 - PHYSICAL / CHEMICAL PROPERTIES

APPEARANCE & ODOR:

Golden-brown, transparent liquid with no significant odor.

ODOR THRESHOLD:

N/A

pH:

13.5 - 14.0 (upstream concentrate value)

MELTING POINT:

N/A

FREEZING POINT:

N/A

BOILING POINT:

210 degrees F.

BOILING POINT RANGE:

N/A

FLASHPOINT:

This product is non-flammable.

EVAPORATION RATE:

N/A

FLAMMABILITY (solid/gas):

N/A



SAFETY DATA SHEET

OCEANSIDE DETAILING PRODUCTS

PREMIUM WHEEL & TIRE CLEANER

EXPLOSION LIMITS:	N/A
VAPOR PRESSURE:	N/A
VAPOR DENSITY (AIR=1):	Greater than 1.
SPECIFIC GRAVITY:	1.06
SOLUBILITY IN WATER:	Completely soluble.
PARTITION COEFFICIENT:	N/A
AUTO-IGNITION TEMPERATURE:	N/A
DECOMPOSITION TEMPERATURE:	N/A
VISCOSITY:	Water thin.

10 - STABILITY AND REACTIVITY

STABILITY:	Stable under normal conditions.
INCOMPATIBILITY:	Do not mix with acids or other detergents. Avoid contact of undiluted product with metals such as zinc, aluminum, tin and brass.
HAZARDOUS DECOMPOSITION:	Carbon oxides, nitrous oxides, sodium oxides, sulfur oxides.
HAZARDOUS POLYMERIZATION:	This product is not known to polymerize.

11 - TOXICOLOGICAL INFORMATION

ROUTE(S) OF ENTRY:	Absorption through skin and eyes. Ingestion. Inhalation.
LISTED CARCINOGEN:	None over 0.1%.
MEDICAL CONDITION AGGRAVATED:	May aggravate pre-existing dermatitis.
INHALATION:	Inhaling significant amounts of undiluted product can cause irritation, burns or other serious damage to the mouth, nose and respiratory tract.
INGESTION:	Undiluted product may be harmful to health and can cause burns or other serious damage to mouth, esophagus and stomach if swallowed.
EYES:	Undiluted product can cause severe irritation, redness, burns, blindness or other permanent damage if not immediately flushed from eyes.
SKIN (DERMAL):	Undiluted product can cause severe irritation, redness and burns if not immediately flushed from skin.
ACUTE TOXICITY (ORAL):	4,187.60 mg/kg
ACUTE TOXICITY (DERMAL):	>5,000 mg/kg
ACUTE TOXICITY (INHALATION):	>20,000 ppm V (Gas), >20 mg/L (Vapor), >5 mg/L (Dust)

*Acute toxicity values are upstream mixture values determined using the additivity formula for mixtures (GHS Purple Book, 3.1.3.6).

12 - ECOLOGICAL INFORMATION

ENVIRONMENTAL FATE AND DISTRIBUTION:	N/A
--------------------------------------	-----

13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:	As recommended by local, state and federal authorities.
-----------------	---

14 - TRANSPORTATION INFORMATION

DOT HMR PROPER SHIPPING NAME:	Compounds, cleaning liquid (contains Sodium hydroxide)
DOT HAZARD CLASS:	8
DOT NA NUMBER:	NA 1760
DOT PACKING GROUP:	III
IMDG PROPER SHIPPING NAME:	SODIUM HYDROXIDE SOLUTION
IMDG HAZARD CLASS:	8
IMDG UN NUMBER:	UN 1824
IMDG PACKING GROUP:	III
IATA PROPER SHIPPING NAME:	Sodium hydroxide solution
IATA HAZARD CLASS:	8
IATA UN NUMBER:	UN 1824
IATA PACKING GROUP:	III

Transport classifications above are from the upstream concentrate SDS. They must be re-evaluated for the actual finished Oceanside dilution before shipping.

15 - REGULATIONS

OSHA HAZCOM:	Upstream SDS states compliance with OSHA Hazard Communication Standard 29 CFR 1910.1200.
--------------	--



SAFETY DATA SHEET

OCEANSIDE DETAILING PRODUCTS

PREMIUM WHEEL & TIRE CLEANER

CALIFORNIA PROPOSITION 65:

WARNING: This product can expose you to chemicals including 1,4-Dioxane, which is known to the State of California to cause cancer, and Methanol, which is known to cause birth defects or other reproductive harm. See www.P65Warnings.ca.gov.

PROP 65 SOURCE LIST:

1,4-Dioxane (CAS 123-91-1); Methanol (CAS 67-56-1); Formaldehyde (CAS 50-00-0); Ethylbenzene (CAS 100-41-4); Nitrotriacetic acid, trisodium salt monohydrate (CAS 18662-53-8).

16 - OTHER INFORMATION

NFPA HEALTH:

3

NFPA FLAMMABILITY:

0

NFPA REACTIVITY:

1

NFPA OTHER:

Alkali

OCEANSIDE PREPARATION DATE:

08/26/2026

SOURCE REVISION DATE:

12/20/2024

DOCUMENT STATUS:

Draft 1.0 - prepared from upstream safety data. Final finished-mixture classification, physical properties, transportation classification, and emergency response number must match the Oceanside product as sold.