



SAFETY DATA SHEET

OCEANSIDE DETAILING PRODUCTS

PREMIUM SPRAY WAX

DRAFT - EMERGENCY RESPONSE SERVICE PENDING

1 - PRODUCT IDENTIFICATION

PRODUCT NAME: Oceanside Detailing Products Premium Spray Wax
PRODUCT TYPE: Neutral Liquid Vehicle Dressing
PRODUCT IDENTIFIER: Premium Spray Wax
PRODUCT NUMBER: ODP-SW
RESPONSIBLE PARTY: Oceanside Detailing Products
ADDRESS: PO Box 229, Deep River, CT 06417
BUSINESS PHONE: 860-333-8675
WEBSITE: www.oceansidedetailingproducts.com
EMERGENCY PHONE: CHEMTREC - pending registration/authorization. Insert authorized emergency number before final commercial distribution.

2 - HAZARDS IDENTIFICATION

CLASSIFICATION OF SUBSTANCE/MIXTURE: Non-hazardous mixture per OSHA Hazard Communication Standard 29 CFR 1910.1200.

3 - COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT	C.A.S. NUMBER
Water	7732-18-5
Polydimethylsiloxane	63148-62-9

If percentages, chemical names, or C.A.S. numbers of ingredients are not listed/shown, they may be withheld as trade secret information or may not require disclosure under OSHA Hazard Communication Standard 29 CFR 1910.1200. Information will be disclosed as necessary to authorized individuals.

4 - FIRST-AID MEASURES

BREATHING (INHALATION): Not likely to be inhaled in hazardous amounts. Maintain adequate ventilation in the work area. If signs of discomfort or irritation occur, remove to fresh air. If symptoms persist, seek medical attention.

SWALLOWING (INGESTION): DO NOT INDUCE VOMITING. Drink a large quantity of water or milk. Do not attempt to give liquids to an unconscious person. Seek medical attention.

EYES: Flush eyes with a large quantity of fresh water for at least 15 minutes. If irritation occurs, seek medical attention.

SKIN (DERMAL): Not likely to irritate. Flush from skin and clothing with large amounts of fresh water. If irritation occurs, discontinue use and seek medical attention. Wash contaminated clothing before reuse.

5 - FIRE-FIGHTING MEASURES

FLASHPOINT: This product is non-flammable.

EXTINGUISHING MEDIA: Use extinguishing media suitable for materials already burning.

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters working in areas where this product is present should be equipped with an approved, fully enclosed SCBA.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None known.

6 - ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES: Dike to prevent spillage into streams or sewer systems. Consult local, state and federal authorities.

WASTE DISPOSAL: As recommended by local, state and federal authorities.

7 - HANDLING AND STORAGE

STORAGE: Store in a cool, well-ventilated area. Avoid overheating or freezing. Do not store this product in an unmarked container.

HANDLING: Wear eye protection if product is likely to splash. Do not transfer this product to an unmarked container. Spilled material is slippery. Keep away from children.



SAFETY DATA SHEET

OCEANSIDE DETAILING PRODUCTS

PREMIUM SPRAY WAX

8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION: Not usually needed. Vapors not normally harmful.
PROTECTIVE CLOTHING: Special protection not usually needed. Wear eye protection if product is likely to splash.
ADDITIONAL MEASURES: Avoid eye contact. Keep away from children.

INGREDIENT	C.A.S. NUMBER	EXPOSURE LIMIT
Water	7732-18-5	No limits established
Polydimethylsiloxane	63148-62-9	No limits established

*When OSHA 8-hour TWA, STEL, and Ceiling PEL values are not established, NIOSH REL, ACGIH TLV, and AIHA WEEL values may be shown in that order, as indicated by the source SDS.

9 - PHYSICAL / CHEMICAL PROPERTIES

APPEARANCE & ODOR: Blue opaque liquid, bubblegum scented.
ODOR THRESHOLD: N/A
pH: 6.0 - 8.0
MELTING POINT: N/A
FREEZING POINT: N/A
BOILING POINT: 210 degrees F.
BOILING POINT RANGE: N/A
FLASHPOINT: This product is non-flammable.
EVAPORATION RATE: N/A
FLAMMABILITY (solid/gas): N/A
EXPLOSION LIMITS: N/A
VAPOR PRESSURE: N/A
VAPOR DENSITY (AIR=1): Greater than 1.
SPECIFIC GRAVITY: 1.00
SOLUBILITY IN WATER: Completely soluble.
PARTITION COEFFICIENT: N/A
AUTO-IGNITION TEMPERATURE: N/A
DECOMPOSITION TEMPERATURE: N/A
VISCOSITY: Water thin

10 - STABILITY AND REACTIVITY

STABILITY: Stable under normal conditions.
INCOMPATIBILITY: Do not mix with other detergents or chemicals.
HAZARDOUS DECOMPOSITION: Carbon Oxides, Silicone Oxides, Nitrous Oxides.
HAZARDOUS POLYMERIZATION: This product is not known to polymerize.

11 - TOXICOLOGICAL INFORMATION

ROUTE(S) OF ENTRY: Absorption through eyes. Ingestion. Not likely to be inhaled or absorbed through skin in hazardous amounts.
LISTED CARCINOGEN: None over 0.1%.
MEDICAL CONDITION AGGRAVATED: None known.
INHALATION: Inhaling significant amounts of this product may eventually cause irritation to the respiratory tract.
INGESTION: This product may cause irritation to the mouth, esophagus and stomach if ingested.
EYES: This product may cause mild irritation and redness if not immediately flushed from the eyes.
SKIN (DERMAL): This product may eventually cause irritation and redness to the exposed area after prolonged contact.
ACUTE TOXICITY (ORAL): >5,000 mg/kg
ACUTE TOXICITY (DERMAL): >5,000 mg/kg
ACUTE TOXICITY (INHALATION): >20,000 ppm V (Gas), >20 mg/l (Vapor), >5 mg/l (Dust)

*Acute toxicity values are supplier-reported mixture values determined using the additivity formula for mixtures (GHS Purple Book, 3.1.3.6).

12 - ECOLOGICAL INFORMATION



SAFETY DATA SHEET

OCEANSIDE DETAILING PRODUCTS

PREMIUM SPRAY WAX

ENVIRONMENTAL FATE AND DISTRIBUTION:

N/A

13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:

As recommended by local, state and federal authorities.

14 - TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME:

Not regulated for domestic shipments according to DOT HMR.

DOT HAZARD CLASS / UN-NA NUMBER / PACKING GROUP:

Not regulated / N/A

IMDG PROPER SHIPPING NAME:

Not regulated for international shipments according to IMDG Code.

IMDG HAZARD CLASS / UN NUMBER / PACKING GROUP:

Not regulated / N/A

IATA PROPER SHIPPING NAME:

Not regulated for international shipments according to IATA DGR.

IATA HAZARD CLASS / UN NUMBER / PACKING GROUP:

Not regulated / N/A

15 - REGULATIONS

OSHA HAZCOM:

Contents of this SDS comply with OSHA Hazard Communication Standard 29 CFR 1910.1200.

CALIFORNIA PROPOSITION 65:

WARNING: This product can expose you to chemicals including Ethylene Oxide, which is known to the State of California to cause cancer, birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

PROP 65 INGREDIENT:

Ethylene Oxide (CAS 75-21-8).

16 - OTHER INFORMATION

NFPA HEALTH:

0

NFPA FLAMMABILITY:

0

NFPA REACTIVITY:

0

NFPA OTHER:

None

OCEANSIDE PREPARATION DATE:

08/26/2026

PRIMARY SOURCE:

Simoniz USA, Inc. Detailer's Choice, D0872XXX.

SOURCE REVISION DATE:

03/22/2024

IMPORTANT DRAFT NOTE: This document is prepared for Oceanside Detailing Products using the source Simoniz SDS information. Insert the authorized emergency-response number before final distribution.