



SAFETY DATA SHEET

OCEANSIDE DETAILING PRODUCTS

PREMIUM CERAMIC SEALANT

DRAFT - EMERGENCY RESPONSE SERVICE AND FINISHED-FORMULATION CLASSIFICATION TO BE CONFIRMED

1 - PRODUCT IDENTIFICATION

PRODUCT NAME: Oceanside Detailing Products Premium Ceramic Sealant
PRODUCT TYPE: Liquid Vehicle Dressing / Ceramic Sealant
PRODUCT IDENTIFIER: Premium Ceramic Sealant
PRODUCT NUMBER: ODP-CS
RESPONSIBLE PARTY: Oceanside Detailing Products
ADDRESS: PO Box 229, Deep River, CT 06417
BUSINESS PHONE: 860-333-8675
WEBSITE: www.oceansidedetailingproducts.com
EMERGENCY PHONE: CHEMTREC - pending registration/authorization. Insert the authorized emergency number before final commercial distribution.

2 - HAZARDS IDENTIFICATION



CLASSIFICATION OF SUBSTANCE/MIXTURE: Eye Irritation (2); Skin Irritation (3)

SIGNAL WORD: WARNING!

HAZARD STATEMENTS: Causes serious eye irritation. Causes mild skin irritation.

PREVENTION: Wash hands thoroughly after handling. Do not touch eyes. Wear eye protection / face protection.

RESPONSE: If skin irritation occurs: Get medical help. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical help.

STORAGE: N/A

DISPOSAL: N/A

3 - COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT

C.A.S. NUMBER

Water	7732-18-5
2-Butoxyethanol	111-76-2
Silicone Quaternary Compound	Mixture / Not Listed

If percentages, chemical names, or C.A.S. numbers are not listed, they may be withheld as trade secret information or may not require disclosure under the OSHA Hazard Communication Standard. Information is to be disclosed as required to authorized individuals.

4 - FIRST-AID MEASURES

BREATHING (INHALATION): If signs of discomfort or irritation occur, remove to fresh air. If symptoms persist, get immediate medical attention.

SWALLOWING (INGESTION): DO NOT INDUCE VOMITING. Drink a large quantity of water or milk. Do not attempt to give liquids to an unconscious person. Get immediate medical attention.

EYES: Flush eyes with a large quantity of fresh water for at least 15 minutes. If irritation persists, consult a physician.

SKIN (DERMAL): Flush skin and contaminated clothing with large amounts of fresh water. If irritation persists, consult a physician. Wash contaminated clothing before reuse.

5 - FIRE-FIGHTING MEASURES

FLASHPOINT: This product is non-flammable.

EXTINGUISHING MEDIA: Use extinguishing media suitable for materials already burning.

SPECIAL FIRE-FIGHTING PROCEDURES: Firefighters working in areas where this product is present should be equipped with an approved, fully enclosed SCBA.

UNUSUAL FIRE / EXPLOSION HAZARDS: None known.

6 - ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES: Dike to prevent spillage into streams or sewer systems. Consult local, state and federal authorities.

WASTE DISPOSAL: As recommended by local, state and federal authorities.



SAFETY DATA SHEET

OCEANSIDE DETAILING PRODUCTS

PREMIUM CERAMIC SEALANT

7 - HANDLING AND STORAGE

STORAGE:	Store in a cool, well-ventilated area. Avoid overheating or freezing.
HANDLING:	Under normal use according to label instructions, special protection should not be necessary. Wear eye protection if product is likely to splash. Do not place this product in an unmarked container. Keep away from children. Spilled material is slippery.

8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION:	Not usually needed in well-ventilated areas. If needed, use a NIOSH-approved respirator.
PROTECTIVE CLOTHING:	Nitrile or PVC gloves and chemical splash goggles.
ADDITIONAL MEASURES:	Wear eye protection if product is likely to splash. Do not place this product in an unmarked container. Keep away from children. Spilled material is slippery.
2-BUTOXYETHANOL EXPOSURE LIMIT:	Supplier SDS historically reports 20 ppm TLV / 50 ppm OSHA PEL for the component.

9 - PHYSICAL / CHEMICAL PROPERTIES

APPEARANCE & ODOR:	Transparent purple liquid; lavender fragrance.
ODOR THRESHOLD:	N/A
pH:	7.5-9.0
MELTING POINT:	210 degrees F (as reported by supplier source).
FREEZING POINT:	N/A
BOILING POINT:	210 degrees F
BOILING POINT RANGE:	N/A
FLASHPOINT:	This product is non-flammable.
EVAPORATION RATE:	N/A
FLAMMABILITY (solid/gas):	N/A
EXPLOSION LIMITS:	N/A
VAPOR PRESSURE:	N/A
VAPOR DENSITY (AIR=1):	Greater than 1
SPECIFIC GRAVITY:	0.99
SOLUBILITY IN WATER:	Completely soluble
PARTITION COEFFICIENT:	N/A
AUTO-IGNITION TEMPERATURE:	N/A
DECOMPOSITION TEMPERATURE:	N/A
VISCOSITY:	Slight body

10 - STABILITY AND REACTIVITY

STABILITY:	Stable under normal conditions.
HAZARDOUS DECOMPOSITION / POLYMERIZATION:	This product is not known to polymerize.
INCOMPATIBILITY:	Do not mix with other chemicals.

11 - TOXICOLOGICAL INFORMATION

ROUTE(S) OF ENTRY:	Absorption through skin and eyes; ingestion. Not likely to be inhaled in hazardous amounts.
LISTED CARCINOGEN:	No chemicals at 0.1% or more are identified by the supplier as listed/classified carcinogens by NTP, IARC, OSHA, or ACGIH.
MEDICAL CONDITION AGGRAVATED:	May aggravate pre-existing dermatitis in people with sensitive skin.
INHALATION:	Not likely to be inhaled in hazardous amounts. Significant exposure to undiluted product may irritate the respiratory tract.
INGESTION:	Undiluted product may irritate the mouth, esophagus, and stomach if ingested.
EYES:	Undiluted product can cause serious irritation and redness if not immediately flushed from eyes.
SKIN (DERMAL):	Undiluted product can cause mild irritation and redness if not flushed from skin.
ACUTE TOXICITY (ORAL):	>5,000 mg/kg



SAFETY DATA SHEET

OCEANSIDE DETAILING PRODUCTS

PREMIUM CERAMIC SEALANT

ACUTE TOXICITY (DERMAL):

>5,000 mg/kg

ACUTE TOXICITY (INHALATION):

>20,000 ppm V (Gas), >20 mg/L (Vapor), >5 mg/L (Dust)

*Acute toxicity values are supplier-reported mixture values determined using the additivity formula for mixtures (GHS Purple Book, 3.1.3.6).

12 - ECOLOGICAL INFORMATION

ENVIRONMENTAL FATE AND DISTRIBUTION:

N/A

13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:

As recommended by local, state and federal authorities.

14 - TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME:

Not regulated for domestic shipments according to the supplier SDS.

HAZARD CLASS:

N/A

UN/NA NUMBER:

N/A

PACKAGING GROUP:

N/A

15 - REGULATIONS

Supplier SDS states that the product SDS complies with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

16 - OTHER INFORMATION

NFPA HEALTH:

1

NFPA FLAMMABILITY:

0

NFPA REACTIVITY:

0

NFPA OTHER:

None

OCEANSIDE PREPARATION DATE:

08/26/2026

PRIMARY SOURCE:

Simoniz USA, Inc. Ceramic Sealant, S0522XXX.

SOURCE STATUS:

Current product identification/hazard/composition information based on the Simoniz Ceramic Sealant source supplied by the user; downstream sections cross-checked against Simoniz S0522 SDS source material.

IMPORTANT DRAFT NOTE: This document is not a final commercial SDS if Oceanside Detailing Products changes the supplier formulation or sells the product at a different dilution than the upstream S0522 product. The finished-mixture hazard classification must accurately reflect the product actually placed on the market. Insert the authorized emergency-response number before final distribution.